

HARVARD METHANE INITIATIVE · RESEARCH RETREAT

GRAZE-Tags

An electronic nose for continuous methane monitoring on cattle



Haritosh Patel · Aizenberg Lab & Murthy Lab
Harvard SEAS · October 16, 2026

Enteric methane is hard to measure at scale

Respiration chambers

Gold standard, but expensive and they isolate animals. Extremely low throughput.

GreenFeed


Easier, but still low throughput, and cows must visit a feeder.

SF₆ tracer

More scalable, but invasive, labor-intensive, and no real-time feedback.

Typical studies: 10–50 animals, a narrow time window, periodic sampling.

Our approach: copy how a nose works



Biology

Smell receptors each respond to many odors. The brain reads the pattern across all of them.

Electronic nose

Several imperfect sensors plus machine learning, reading the pattern of their signals.

The sensing element: a heated metal oxide

1

Gas arrives

Air drifts onto a small chip with a metal-oxide surface kept hot.

2

It reacts

Methane and other gases react with oxygen on the oxide surface.


3

Resistance drops

The electrical change is the signal: bigger change, more gas.

Cheap, tiny, low power. But it is not choosy: it reacts to many gases.

The catch: it responds to everything



2×


Pentane beats methane

A common farm VOC gives about twice methane's signal at the same 1,000 ppm.

Barns are full of VOCs


Manure, silage and animal breath release pentane, acetone, toluene and more.

The fix: a filter in front of the sensor



Small, weakly sticky methane diffuses through. Larger VOCs get trapped.

With the filter, only methane is seen



2,500×

Less pentane signal


Interferents fall below the sensor's noise.

7.8 ppm

Detection limit

A clean, linear methane response,
 $R^2 = 0.999$.

Three sensors, one board



Methane-selective

The filtered sensor you just saw.


General VOC

Tracks interfering gases.

CO₂, temperature, humidity

Context. Humidity cuts the signal by over half across 4–81% RH, but predictably, so it is corrected.

Packaged as an ear tag



Breathes, stays dry

Slanted vents plus a hydrophobic PTFE membrane.

Wireless and solar

About the size of a commercial GPS cattle tag.

Battery: the open problem

About 2 weeks in simulation. Lower-power sensors project 3× or more.

The Davis study: a cow's whole life

At UC Davis, Prof. Ermias Kebreab's lab:

Male dairy calves followed from birth to slaughter on a seaweed-based methane-reducing additive.

8

Control

Typical diet, no additive.

8

Short-term

Additive until 3 weeks after weaning, then withdrawn.


8

Life-time

Additive from weaning until slaughter.

About 18 months across three facilities. Calves enroll 2–4 per month.

First field test: June to November 2026



Setup

Two tags beside a GreenFeed unit, installed ~June 16. Data flow wirelessly to cloud database.

57.2 g

First match

Signal dips line up with GreenFeed events of 57.2 g and 67.5 g. Data continue through November.

What the Davis data will tell us

1

Agreement

Does the tag signal track
GreenFeed readings animal by
animal?

2

Treatment contrast

Can tags see a difference
between control and additive-fed
cattle?

3

Durability

Do two tags stay consistent over
months outdoors?

Planned analyses; update as results come in.

Policy is moving toward measurement

40%

California

SB 1383: dairy and livestock methane 40% below 2013 levels by 2030. CARB began information gathering in January 2026.

2026

United States

EMIT LESS Act proposed for the 2026 Farm Bill. USDA is building enteric methane research capacity.

2024

European Union

Regulation 2024/1787 mandates methane measurement for energy. Livestock approaches are under review.

Where we go next

1

Harden and shrink

Rain, dust and impact testing. Miniaturize, extend battery life.

2

Model the air

Airflow simulations to link a signal to a specific cow.

3

Freely moving cows

Longer validation on grazing and barn animals.

4

Commercialize

Partners, manufacturing, calibration.

We welcome herd partners and policy input.

A sensor on every cow, measuring all the time

Low-cost

Lightweight

Wireless & Solar-powered